

Wheel Balancers

DST-2420 FEATURES:

- Dynamic, Static and Performance Alloy settings
- Automatic round-off with top-dead-center weight position indicator
- Hardened-steel 36 mm shaft
- Quick-release hub nut
- Multi-user save function

DST-30P FEATURES:

- Ergonomic control board and easy-to-read LED display
- Multi-user save function
- Automatic braking
- Low RPM balancing speed and rapid six-second cycle time
- Self-calibration function

DST-64T FEATURES:

- Precision DataWand™ and inner data arm
- Low RPM balancing speed and rapid six-second cycle time
- Automatic braking
- LED inner wheel target light
- Manual or automatic start
- Self-calibration function



**DST-2420
Wheel Balancer**
5140200

Max. Wheel Diameter - 10" - 30"
Max. Tire Diameter - 47"
Max. Tire Weight - 145 lbs.



**DST-30P
Wheel Balancer**
5140300

Max. Wheel Diameter - 8" - 30"
Max. Tire Diameter - 50"
Max. Tire Weight - 150 lbs.



**DST642D
Wheel Balancer**
5140305

Max. Wheel Diameter - 10" - 30"
Max. Tire Diameter - 50"
Max. Tire Weight - 150 lbs.



**DST-64T
Wheel Balancer**
3D Quick-Touch™
DataWand™
5140240

Max. Wheel Diameter - 10" - 30"
Max. Tire Diameter - 50"
Max. Tire Weight - 150 lbs.



**RB24T
Truck Wheel Balancer**
5140235

Max. Wheel Diameter - 30"
Max. Tire Diameter - 50"
Max. Tire Weight - 400 lbs.



**Adhesive Steel
Wheel Weights
Silver**
5150220



700 Pcs. Per Roll
Weight - 7g (.25oz) ea. / Width - 1.5"
Strong Adhesive Backing



**Adhesive Steel
Wheel Weights
Black**
5150225



700 Pcs. Per Roll
Weight - 7g (.25oz) ea. / Width - 1.5"
Strong Adhesive Backing



**Adhesive Steel
Wheel Weights
Combo**
5150230



1400 Pcs. Per Roll
Weight - 7g (.25oz) ea. / Width - 1.5"
Strong Adhesive Backing

Laser-Spot Balancer

INFORMATION:

The Ranger LS43B wheel balancer handles wheels up to 43 inches in diameter. The average cycle time is just 7 seconds, making it one of the fastest and most reliable balancing machines ever built. The standout feature on this model, of course, is Ranger's exclusive 3D Quick-Touch™ Laser-Spot™ technology that highlights the pinpoint location at which operators should place the minimal amount of weight in order to achieve a perfect balance at the 6 o'clock position. Ranger makes it easy to seamlessly determine the exact weight placement position. Only a single weight placement should be necessary for most wheel and tire configurations.

LS43B FEATURES:

- Dynamic, Static and Performance Alloy settings
- Low RPM balancing speed and rapid six-second cycle time
- Manual or automatic start when hood is lowered
- Self-calibration function
- Automatic braking

LS43B Wheel Balancer 3D Quick-Touch™ Laser-Spot™

5140121

Max. Wheel Diameter - 10" - 30"
 Max. Tire Diameter - 47"
 Max. Tire Weight - 145 lbs.



INCLUDES TOOLING KIT



OPTIONAL Clip-On Steel Wheel Weights

Sold separately



25 ea.

0.25oz, 0.50oz, 0.75oz, 1oz, 1.25oz, 1.5oz,
 1.75oz, 2oz, 2.25oz, 2.5oz, 2.75oz, 3oz