The QuickJack portable lifting system makes vehicle maintenance on and off the track convenient and lightning fast. The QuickJack can go anywhere and is easily stowed in the trunk or back seat of most cars. Bring it to the track, or drop it on your garage floor to perform routine maintenance in the comfort of your home, all in seconds. The QuickJack replaces clumsy floor jacks and unstable jack stands with a safe, durable and convenient vehicle jacking and support system. Simply position the lightweight jack frames under the vehicle, push the raise button on the hand-held pendant control, and in seconds the entire car is about 21" off the ground, ready for tire changes, chassis tuning or other maintenance.

The ruggedly built frames collapse to a low three-inch profile, so they fit where other jacks and lifts don't. With QuickJack, practicality and portability become reality. Because the QuickJack is void of any cross members, it provides total undercar access and can be installed at a width that best suits the vehicle being raised.

QUICKJACK[™]

The Ultimate Car Jack and Support System

- Sets up in seconds
- Safe & durable
- Easy to use
- Portable

3″ collapsible height

QUICKJACK[™]

110V-AC power unit standard. Optional 12V-DC & 220V-AC available.

> ©2017 QuickJack LLC. A BendPak company. QuickJack products are protected by one or more patents in the United States, China, Europe, and other countries.

3,500 / 5,000 / 7,000 LBS. CAPACITY

3,500 / 5,000 / 7,000 LBS. CAPACITY

See it on You YouTube Tube

Specification

You get it all

(2) Ea. Jack Frame Assemblies

(2) Ea. Quick-Mount

Handles

Rubber Blocks

5 MODELS TO CHOOSE FROM

RE

Optional

SUV & Light Truck Adapters

TOYOTA

*shown with optional adapters

BL-7000EXT 7,000 lbs. / 3,175 kg

101 lbs. / 46 kg

18.2["]/462 mm

21.5" / 546 mm

37.4["]/951 mm

66" / 1,676 mm

12.5["]/ 318 mm

76" / 1,930 mm

15-30 seconds

3.6″/91 mm

٢g

specifications.		
	BL-3500SLX	BL-5000SLX
Lifting Capacity	3,500 lbs. / 1,588 kg	5,000 lbs. / 2,26
Individual Frame Weight	60 lbs. / 27 kg	76 lbs. / 35 kg
Raised (frame only)	16.5″ / 419 mm	17.6″ / 447 mm
Raised (stacked blocks)	20″ / 508 mm	21.3 [″] / 542 mm
Collapsed	3″/ 75 mm	3″ / 75 mm
Lifting Point Spread - MIN	26.7″ / 678 mm	29.5 [″] / 749 mm
Lifting Point Spread - MAX	50.5″/ 1,283 mm	60″ / 1,524 mm
Frame Width	10.6″/ 268 mm	11″ / 278 mm
Frame Length	62″/ 1,575 mm	70″ / 1,778 mm
Lifting Time	15-30 seconds	15-30 seconds

(4) Ea. 3" x 3" x 4"

Rubber Blocks

(2) Ea. 150" Hydraulic Hoses

(1) Ea. Mini Hydraulic Power Unit. 110V-AC

Standard. Includes

Pendant Control. (Optional 12V-DC and . 220V-AC Available)

HTS RESERVE

PATENTED

(2) Ea. 14["]Aux. Hoses

BL-5000SLX	BL-5000EXT	BL-7000SLX
5,000 lbs. / 2,268 kg	5,000 lbs. / 2,268 kg	7,000 lbs. / 3,175 k
76 lbs. / 35 kg	80 lbs. / 36 kg	96 lbs. / 44 kg
17.6″ / 447 mm	17.6″ / 447 mm	18.2″/ 462 mm
21.3″/ 542 mm	21.3″ / 542 mm	21.5″/ 546 mm
3″ / 75 mm	3″ / 75 mm	3.6″/ 91 mm
29.5″ / 749 mm	35.5″ / 902 mm	29.5″ / 749 mm
60″/ 1,524 mm	66″/ 1,676 mm	60″ / 1,524 mm
11″ / 278 mm	11″/ 278 mm	12.5″ / 318 mm
70″ / 1,778 mm	75″ / 1,905 mm	70″ / 1,778 mm
15-30 seconds	15-30 seconds	15-30 seconds

Must Have

4-in-1 Portable **Power Pack**

- ✓ 12V Jump Starter
- ✓ Air Compressor
- ✓ LED Flashlight
- ✓ USB Charger

JACKPAK **ETH** JACKPAK

OUICKJACK[™]